



公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	公差 (mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10	±Z				
3	~	~	~	~	~	~	~	~	~	~	~	~	~						
6	~	~	~	~	~	~	~	~	~	~	~	~	~						
10	~	~	~	~	~	~	~	~	~	~	~	~	~						
18	~	~	~	~	~	~	~	~	~	~	~	~	~						
30	~	~	~	~	~	~	~	~	~	~	~	~	~						
50	~	~	~	~	~	~	~	~	~	~	~	~	~						
80	~	~	~	~	~	~	~	~	~	~	~	~	~						
120	~	~	~	~	~	~	~	~	~	~	~	~	~						
180	~	~	~	~	~	~	~	~	~	~	~	~	~						
250	~	~	~	~	~	~	~	~	~	~	~	~	~						
315	~	~	~	~	~	~	~	~	~	~	~	~	~						
400	~	~	~	~	~	~	~	~	~	~	~	~	~						
500	~	~	~	~	~	~	~	~	~	~	~	~	~						
±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50	±2.50						

MATERIAL:		SURFACE:	
MAT NO.:		<b>宁波三安电子科技有限公司</b> Sanan Electrical Technology Co. Ltd	
STATUS:		NAME:	15ESAK-3.81-XXP-1Y-00A(H)
APPD:		DRAWING NO.:	
CHKD:		SCALE:	1/1
DRT:		REV:	
SIZE: A4	mm / inch	SHEET:	1/1

ITEM	NAME OF PART	MATERIAL	NOTES
5	Clamp	Copper Alloy	Sn Plated
4	Screw	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

  

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8	/	300/8
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	II/2		
额定电压/电流 / Rated Voltage(V)/Current(A)	250/7		
额定冲击电压 (KV) / Rate Impulse Voltage (KV)	2.5		
螺栓扭矩 / Torque Tightening (N·m/Lb.in)	M2: 0.2/1.77		
导线范围 (硬线和软线) / Wire Range (rigid and flexible) (mm <sup>2</sup> /AWG)	0.5~1.5/28~16		
剥线长度 / Stripping length (mm)	3.81 N=02~24P		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		